



VIBFAST PIGMENTS PVT. LTD.



C-1, 91/6, Phase I, B/h. Bank of India,
G.I.D.C., Vatva, Ahmedabad - 382 445. (India)
Phone : +91-79-3292 0774, 6450 1424 Fax : +91-79-25893014

E-mail : amit@vibgyorchemtex.com
• amit@vibfast.com • amit@vibfastcolour.com
Website : www.vibgyorchemtex.com • www.vibfast.com

TECHNICAL DATA SHEET	
NAME OF THE PRODUCT	SOLVENT RED 24
C. I. HUE NAME	SOLVENT RED 24
C.I. NUMBER	26105
CHEMICAL CLASS	DISAZO
HUE	RED-BLUIISH RED POWDER
PHYSICAL APPEREANCE	BLACKISH RED POWDER
PH	7 TO 8
SOLUBILITY	SOLUBLE IN ETHANOL & ACETONE VERY SOLUBLE IN BENZENE.
LOVIBOND TINTOMETER READING 0.002% COLOUR IN BENZENE IN 1/4 INCH CELL	YELLOW 0.2 ± 0.2 RED 11.0 ± 0.2
LEAD CONTENTS	LESS THAN 20 PPM
ARSENIC CONTENTS	LESS THAN 2 PPM
HEAVY METAL CONTENTS	LESS THAN 100 PPM
FASTNESS	
LIGHT	GOOD
HEAT : MELTING POINT : STABLE TO	$172^{\circ}\text{C} \pm 2$ 120°C (MINERAL OIL)
WATER	INSOLUBLE
EFFECT OF 5% NA_2CO_3	UNAFFECTED
EFFECT OF 5% HCL	UNAFFECTED
MATERIAL SUPPLIED AS	HEAVY PAPER BAGS/ M.S. DRUMS / HDPE CARBOYS INSIDE DOUBLE POLYTHELENE BAGS
USES	IN HYDROCARBON SOLVENTS. OILS, FATS, AND WAXES FOR SHOE AND FLOOR POLISHES IN PETROL, OILS, AND GREASES, WOOD STAINS.