



VIBFAST PIGMENTS PVT. LTD.



C-1, 91/6, Phase I, B/h. Bank of India,
G.I.D.C., Vatva, Ahmedabad - 382 445. (India)
Phone : +91-79-3292 0774, 6450 1424 Fax : +91-79-25893014

E-mail : amit@vibgyorchemtex.com
* amit@vibfast.com * amit@vibfastcolour.com
Website : www.vibgyorchemtex.com * www.vibfast.com

TECHNICAL DATA SHEET

Product Name	VIBASOL VIOLET VT
Color Index	Solvent Violet 13
Delivery Form	Powder
CAS	81-48-1

Physical and Chemical properties

Test Items	Specification
Appearance	Violet powder
Heat Resistance, °C	260
Light Fastness	6-7
Acid Resistance	5
Alkali Resistance	5
Density, g/cm ³	1.35
Residue on 80mesh, %	5.0 max.
Water Soluble, %	1.0 max.
Volatile Matter at 105°C, %	1.0 max.
Tinting Strength, %	100% ± 5%

Application

Colouring for polystyrene, hard polystyrene and various resins, fiber, plastic, PS, HIPS, ABS, PC, RPVC, PMMA, SAN, AS, PET, also used to color protoplasm of terylene and fibre.

Package

25kg bag, 25kg carton box, 25kg drum with pallets.