



# VIBFAST PIGMENTS PVT. LTD.



C-1, 91/6, Phase I, B/h. Bank of India,  
G.I.D.C., Vatva, Ahmedabad - 382 445. (India)  
Phone : +91-79-3292 0774, 6450 1424 Fax : +91-79-25893014

E-mail : amit@vibgyorchemtex.com  
\* amit@vibfast.com \* amit@vibfastcolour.com  
Website : www.vibgyorchemtex.com \* www.vibfast.com

## TECHNICAL DATA SHEET

**PRODUCT C.I. NAME.** : **PIGMENT YELLOW 12**  
**VIBFAST YELLOW 4004-T**  
**C.I. NO.** : **21090**  
**CUST.TARRIF NO.** : **3204 17 19**

### PHYSICAL PROPERTIES

Specific Gravity (24°C) : 1.30  
Moisture Contents : < 1%  
Salt Content : < 1%  
Oil Absorption : ≤45  
Sieve Residue (300 Mesh) : 0.5%  
pH Of Aqueous Extract : 7  
Heat Stability (°C/5min) : 200  
Bulk Volume (L/kg) : 7  
Grit Content : Less than 500 ppm  
Heavy Metal, & PCB Content : Complying to EN 71-3 and AP (89) of European regulation.  
Powder Appearance : Dry Yellow Powder  
Hazardous ingredients : Nil  
Toxicological properties : Non toxic  
Shelf Life : 5 Years

### FASTNESS PROPERTIES (1-5) Scale ; 1 Poor - 5 Excellent

Water : 5  
Xylene : 4-5  
Ethanol : 3-4  
Linseed Oil : 4-5  
Methyl Ethyl Ketone : 4  
Acid : 5  
Alkali : 5

### LIGHT FASTNESS (1-8 Scale ; 1 Very Low - 8 Outstanding)

Full Shade : 6  
Tint Shade : 5-6