



VIBFAST PIGMENTS PVT. LTD.



C-1, 91/6, Phase I, B/h. Bank of India,
G.I.D.C., Vatva, Ahmedabad - 382 445. (India)
Phone : +91-79-3292 0774, 6450 1424 Fax : +91-79-25893014

E-mail : amit@vibgyorchemtex.com
* amit@vibfast.com * amit@vibfastcolour.com
Website : www.vibgyorchemtex.com * www.vibfast.com

TECHNICAL DATA SHEET

Product Name	VIBASOL ORANGE VXG
Color Index	Solvent Orange 63
Appearance	Powder
CAS	16294-75-0

Physical and Chemical properties

Test Items	Specification
Appearance	Orange powder
Heat Resistance, °C	300
Light Fastness	6-7
Acid Resistance	5
Alkali Resistance	5
Density, g/cm ³	1.49
Residue on 80mesh, %	5.0 max.
Water Soluble, %	1.0 max.
Volatile Matter at 105°C, %	1.0 max.
Tinting Strength, %	100% + 5%

Application

Colouring for polystyrene, PS, HIPS, ABS, PC, RPVC, PMMA, SAN, AS, PA6, PET, ABS resin, polymethylmethacrylate, resin, unplasticized pvc and other plastics, also used in coloring of estron, caprone and terylene laser device.

Package

25kg bag, 25kg carton box, 25kg drum with pallets.